
Product data sheet


RING 50 MUTE
RG5MZ-128402-LXXXO
LUX-IT



IP 20


pendant mounted dir-indir LED luminaire;

Light output 1 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 2 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 3 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 4 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 5 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 6 (integrated)




Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 7 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Light output 8 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.91 W	CRI	80
Total flux	882 lm	LOR	100%
Luminous efficacy	128 lm/W	Total power	6.91 W

Mounting mode

Pendant

Shape and measurements

Length: 48.03 in
Width: 48.03 in
Height: 3.15 in

Adjustability

Fixed

Electric

System power: 55.28 W

Protection

IP: 20
Designation labels: CE