

Product data sheet

MINUX 38-6W-930-38°


MINUX

NEKO



Round recessed downlight made of die-cast aluminium; LED Power 6W; measurement Ø45mm; narrow mounting trim with a cutout of Ø38mm; luminaire's height is 84mm; Ceiling Thickness 5-25mm; high color rendering at an index of CRI90; after a lifetime of 50000h L80B10 min. 80% of the luminous flux with energy efficient CITIZEN LED Chips; 5 years warranty; beam characteristic with 38° beam angle; lighting perfectly suitable for reading, writing as well as computer and control work with UGR<19; degree of housing protection IP54 on the visible part of the product one installed; light source replaceable by a qualified electrician; driver replaceable by a qualified electrician

Light output 1 (integrated)



Lamp type	LED	CCT	2913 K
Nominal lamp power	7.71 W	CRI	92
Total flux	470 lm	LOR	90%
Luminous efficacy	61 lm/W	Total power	7.71 W

Mounting mode

Ceiling recessed

Shape and measurements

Height: 3.23 in

Diameter: 1.50 in

Adjustability

Fixed

Design

Material impression: Matt

Color of housing: White

Electric

System power: 7.71 W

Ballast: ECG

Controller: DALI

Protection

IP: 54

Designation labels: CE

Other operating numbers

Ambient temperature range: -4...77°F