


# Product data sheet


SINUS CURVED SEGMENT FRAME BLACK PRISM. 45° R920  
P33-E44-9005E1830L3M OHNE FOLIE/WITHOUT FOIL  
PLANLICHT



IP  
40


low output LED 3000K CRI 90 10,9W 1041lm' DALI 'Values without foil [Luminaire is delivered with optional satined-foil for increased homogeneity. The light distribution is thus influenced and the luminous flux is reduced by 26,3% <https://katalog.planlicht.com/en-gb/search?q=sinus%20segment>

## Light output 1 (integrated)




|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 3.63 W  | CRI         | 90     |
| Total flux         | 347 lm  | LOR         | 100%   |
| Luminous efficacy  | 96 lm/W | Total power | 3.63 W |

## Light output 2 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 3.63 W  | CRI         | 90     |
| Total flux         | 347 lm  | LOR         | 100%   |
| Luminous efficacy  | 96 lm/W | Total power | 3.63 W |

## Light output 3 (integrated)



|                    |         |             |        |
|--------------------|---------|-------------|--------|
| Lamp type          | LED     | CCT         | 3000 K |
| Nominal lamp power | 3.63 W  | CRI         | 90     |
| Total flux         | 347 lm  | LOR         | 100%   |
| Luminous efficacy  | 96 lm/W | Total power | 3.63 W |

**Mounting mode**

Ceiling recessed

**Shape and measurements**

Length: 26.81 in

Width: 13.50 in

Height: 3.23 in

**Adjustability**

Fixed

**Electric**

System power: 10.9 W

**Protection**

IP: 40