



Product data sheet

ECLPARIPMFC
ECLPARIPMFC_RED_WIDE LENS
PROLIGHTS



EclPar IPMFC is a flexible IP rated single source LED spotlight, featuring an 100W RGB+WarmWhite light source with high efficiency and advanced colour control. Its Spektra calibrated LED source delivers a high-quality white reproduction with high CRI and TM30 with an advanced control over colours, ensuring consistency across fixtures. The unit is compact and completely fan free, making the EclPar IPMFC a workhorse for any outdoor and dusty environment, but as well as for corporate and studio whereas silent operations are required. The flexible optical system allow a wide selection of lenses from narrow 15° (on board), flood 30°, and ultra wide 60°, which can be quickly mounted in front of the luminaire or inside the front tempered glass for lasting exterior installation. Features: 100W Spektra calibrated RGB + Warm White LED delivering high CRI, TLCI, TM30 values Flex lens system: 15° on-board - 30° and 60° optional IP65 for exterior application, fan free

Light output 1



1 x LED			
Nominal lamp power	30.8 W	LOR	100%
Lamp flux	973 lm	Total flux	975 lm
Luminous efficacy	32 lm/W	Total power	30.8 W
CCT	0 K		
CRI	-29		

Mounting mode

Ceiling mounted, Standing / Bollard

Shape and measurements

Length: 10.19 in

Width: 2.56 in

Height: 9.74 in

Adjustability

Rotatable, Tilttable, Free

Design

Material impression: Aluminum

Electric

System power: 30.8 W

Controller: DMX

Color adjustable

Appliance Class: I

Protection

IP: 65

IK: 08

Surface temperature: 50°C

Designation labels: CE