

Product data sheet


HBXR L80 LE3
HALOBAY RECESSED LED EMERGENCY
DEXTRA



IP
20


Halobay Surface Surface mounted luminaire, spun aluminium housing, high transmission opal polycarbonate dished diffuser. Options: LE3 - Lithium Emergency (593 lumens output) LS3 - Lithium Selftest LA3 - Lithium Autotest S - Switch Dimming D - Digital Dimming (DSI) A - Digital Addressable Lighting Interface (DALI) C - Bi-Level Dimming (Corridor Function) H - High Frequency Dimming (Analogue 1-10v) RLS - Reacta-Link Wireless Presence

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	45.1 W	CRI	80
Total flux	7360 lm	LOR	100%
Luminous efficacy	163 lm/W	ULOR	4%
		Total power	45.1 W

Light output 2 (integrated, emergency)



Lamp type		CCT	4000 K
Nominal lamp power	4.5 W	CRI	80
Total flux	593 lm	LOR	100%
Luminous efficacy	132 lm/W	ULOR	4%
		Total power	4.5 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 21.65 in

Width: 21.65 in

Height: 2.48 in

Adjustability

Fixed

Electric

System power: 49.6 W

Ballast: ECG

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20