


Product data sheet

ICON 24 LED COMFORT F5T1
4482X5XX
PROLUMIA




Light Source: Philips LumiLEDs Luxeon TX Color temperature: 3000K / 4000K Color rendering index: Ra ≥ 75 Operating temperature: -30°C ~ +50°C Rated life hours: L90 > 100.000 hours LED driver (included): Meanwell / Philips Xitanium Input: 220-240V AC 50/60Hz Power factor: > 0,95

Light output 1




1 x LED

Nominal lamp power	19 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	116 lm/W	Total power	19 W
CCT	4000 K		
CRI	80		




1 x LED

Nominal lamp power	19 W	LOR	100%
Lamp flux	2200 lm	Total flux	2200 lm
Luminous efficacy	116 lm/W	Total power	19 W
CCT	3000 K		
CRI	80		



1 x LED


Nominal lamp power	16 W	LOR	100%
Lamp flux	1300 lm	Total flux	1300 lm
Luminous efficacy	81 lm/W	Total power	16 W
CCT	4000 K		
CRI	80		



1 x LED

Nominal lamp power	17 W
Lamp flux	1300 lm
Luminous efficacy	76 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	1300 lm
Total power	17 W



1 x LED

Nominal lamp power	12 W
Lamp flux	1000 lm
Luminous efficacy	83 lm/W
CCT	4000 K
CRI	80


LOR	100%
Total flux	1000 lm
Total power	12 W



1 x LED

Nominal lamp power	12 W
Lamp flux	1000 lm
Luminous efficacy	83 lm/W
CCT	3000 K
CRI	80


LOR	100%
Total flux	1000 lm
Total power	12 W



1 x LED

Nominal lamp power	25 W
Lamp flux	2800 lm
Luminous efficacy	112 lm/W
CCT	4000 K
CRI	80


LOR	100%
Total flux	2800 lm
Total power	25 W



1 x LED


Nominal lamp power	25 W
Lamp flux	2800 lm
Luminous efficacy	112 lm/W
CCT	3000 K
CRI	80

LOR	100%
Total flux	2800 lm
Total power	25 W



1 x LED

Nominal lamp power	32 W	LOR	100%
Lamp flux	3600 lm	Total flux	3600 lm
Luminous efficacy	112 lm/W	Total power	32 W
CCT	3000 K		
CRI	80		



1 x LED

Nominal lamp power	32 W	LOR	100%
Lamp flux	3600 lm	Total flux	3600 lm
Luminous efficacy	112 lm/W	Total power	32 W
CCT	4000 K		
CRI	80		

Mounting mode

Ceiling mounted, Pole top mounted

Shape and measurements

Height: 10.83 in

Diameter: 22.48 in

Electric

System power: 12-32 W

Appliance Class: 0

Protection

IP: 66

IK: 08

Designation labels: CE