



Product data sheet

ZOUK3 - CVDA
7054-0-7-683-XX
UNILAMP



Low glare, low level surface mounted wall light, Zouk makes it easy to have all the benefits of a brick light without recess the luminaire. Installers will be grateful of this choice. Thanks to the high efficiency LED engine Zouk offers both low glare and high output. Manufactured from LM6 Aluminium the housing is built to last and be situated in the harshest of climates. The double coating of Nano Ceramic ensures longevity. Built with the mindset of light comfort and soft visualization Zouk has no visible mounting screws. With a CRI > 80 and an offering of 2700K, 3000k and 4000k we have taken a view to offer as many options as possible. Available in 3 different shapes to compliment both commercial and residential applications. • Designed, Manufactured and tested according to IEC 60598-1, IEC 60598-2-1 and VDE regulations. • LM6 die-cast aluminium body. • Stainless steel screws. • Nano Ceramic surface conversion. • Double layer coating. • Safety glass cover. • Post-cured silicone gasket. • High quality LED module and driver. • GFR PA6.6 terminal block. • Weather proof grommet. • Installation work has to be carried on according to the enclosed product manual.

Light output 1



| | | | |
|--------------------|----------|-------------|--------|
| 1 x LED | | | |
| Nominal lamp power | 5.9 W | LOR | 100% |
| Lamp flux | 800 lm | ULOR | 7% |
| Luminous efficacy | 136 lm/W | Total flux | 800 lm |
| CCT | 2700 K | Total power | 5.9 W |
| CRI | 80 | | |

Mounting mode

Wall mounted

Shape and measurements

Length: 9.46 in
Width: 1.38 in
Height: 9.47 in

Adjustability

Fixed

Electric

System power: 5.9 W
Controller: DALI
Appliance Class: I

Protection

IP: 65
IK: 07