Product data sheet


SONIS EVO
901649.002.76
RZB



IP 20 IK 03

Series: Sonis EVO Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 Hz, 60 Hz Lay-in luminaire for ceiling systems with visible mounting rails. Housing and cover made of powder-coated sheet steel, anti-glare screen made of plastic (ABS) metallised, highly polished, for grid ceilings (1250mm x 315mm). Lamp (LED) included. Available Colours: white Type of Installation: Recessed ceiling mounting Dimensions: L 1247, B 310, HE 27 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 6200lm System power: 56W Beam Angle: 77°/73° Number of fittings B10A: 10 Number of fittings B16A: 16 Number of fittings C10A: 16 Number of fittings C16A: 26 Inrush current: 26A Unified Glare Ratio: 18,5 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	56 W	CRI	80
Total flux	6200 lm	LOR	100%
Luminous efficacy	111 lm/W	Total power	56 W

Mounting mode

Ceiling recessed

Shape and measurements

Length: 12.20 in
Width: 49.09 in
Height: 1.06 in

Adjustability

Fixed

Electric

System power: 56 W

Protection

IP: 20
IK: 03