Product data sheet


REK 933MM 360º EMISSION
55-E036-Z5-CM
LEDSC4



IP 66 IK 10

LedsC4 Rek 933mm 360º Emission 55-E036-Z5-CM Bollard for outdoor use. Structure material: Aluminium. Structure finish: Urban grey. Diffuser material: Polycarbonate. Diffuser finish: Transparent. UV protection. Warranty: 5 Years. Product net weight (Kg): 5.29 Product width or diameter (mm): 150 Product height (mm): 934 Class 1. IP: IP66. IK: IK10. LED. No. of lampholders or LEDs: 1. LED brand: NICHIA. Driver brand: TCI. Maximum power of light source: 35.9W. Colour temperature: 4000K. Colour rendering index: 80. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 28.2. Photobiological risk: RG1. % de Flickering: +/- 4%. Real flux (lm): 918. Real lm/W: 23. Voltage / frequency range: 220-240/50-60Hz. Voltage: 11.9. Equipment included: Yes. Total power: 40. Power factor: 0.95. Dimmable equipment included: DALI-2.

Light output 1



1 x LED

Nominal lamp power	40 W	LOR	100%
Lamp flux	918 lm	Total flux	918 lm
Luminous efficacy	23 lm/W	Total power	40 W
CCT	4000 K		
CRI	80		

Mounting mode

Standing / Bollard

Shape and measurements

Length: 6.30 in
Width: 6.30 in
Height: 36.73 in

Adjustability

Fixed

Electric

System power: 40 W
Appliance Class: I

Protection

IP: 66
IK: 10