Product data sheet


TEMPLED RAYBEAM LITE V2 200 - 90 5000K
312295
TEMPLED



IP 65 IK 08

LED-Hallenleuchte, modularer Gesamtaufbau mit austauschbaren Komponenten (Netzteil, LED-Lichtfeld, Lichtlenkungsoptik), Leistungsaufnahme: 200 Watt inkl. Vorschaltgerät, Lichtstrom: ca. 36.000 Lumen, Farbtemperatur: 5.000 K, Abstrahlwinkel: 90 Grad, Multifunktionssteckplatz für Sensorsysteme, Hochleistungslichtlenkungsoptik in Linearechnik, Schutzart: IP65, Druckausgleichsmembran, 5 Jahre Garantie, 10 Jahre Ersatzteilgarantie, Eingangsspannung AC: 100-240 VAC - 50/60 Hz, Eingangsspannung DC: 140-250 VDC, weitere Daten gemäß Produktblatt.

Light output 1 (integrated)



Lamp type	LED	CCT	5000 K
Nominal lamp power	200 W	CRI	80
Total flux	36000 lm	LOR	100%
Luminous efficacy	180 lm/W	Total power	200 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 10.31 in
Diameter: 15.79 in

Design

Color of housing: Silver gray

Electric

System power: 200 W
Appliance Class: I

Protection

IP: 65
IK: 08

Other operating numbers

Ambient temperature range: -40...122°F