

# Product data sheet

3F TANK LITE 2X18W/865 L1265


56669

3F FILIPPI



LED luminaire with high mechanical and chemical resistance in tubular form for low temperatures and severe conditions such as ATEX environments. ILLUMINOTECHNICAL Luminous efficiency 100% (DLOR 99%, ULOR 1%). Initial luminous flux of the luminaire 6209 lm. Direct diffused symmetric distribution. Installation Interdistance Transv.D = 1.29 x hu - Long.D = 1.22 x hu. Tabular UGR (CIE 117 - 4H-8H; S=0.25H; 70/50/20): RUG 24.3 - 25.2. Beam angle: 116° - 111°. Luminous efficacy 155 lm/W. Lifetime (L93/B10): 30000 h. (tq+25°C) Lifetime (L90/B10): 50000 h. (tq+25°C) Lifetime (L85/B10): 80000 h. (tq+25°C) Lifetime (L80/B10): 100000 h. (tq+25°C) Lifetime (L85/B10): 50000 h. (tq+40°C) Sudden decreased luminous flux after 50000 hours: 0% (C0). Photobiological safety in compliance with IEC/TR 62778: RG0 risk exempt, (IEC 62471). In compliance with IEC/EN 62722-2-1 - IEC/EN 62717 standards. SOURCE 2 linear LED modules 18W/865. Energy efficiency class (UE 2019/2020 - UE 2019/2015): D. CIE 13.3 Colour rendering index: CRI >80 (R9 <50%). IES TM-30 Fidelity Index: Rf = 84 Rg = 95. CCT nominal colour temperature 6500 K. Colour initial tolerance (MacAdam): SDCM 3. MECHANICAL High thickness tubular body in high transparency polycarbonate surface treatment, which guarantees resistance to aggressive chemical agents. Aluminium 6082-T6 end caps. Sealing gasket. Gear-holder reflector in hot-dip galvanised steel, painted with white polyester base. Fixing brackets and screws in AISI 316 stainless steel. Dimensions: length 1264 mm, diameter 80 mm. Weight 3.45 kg. IP69K protection degree; IP66 ATEX applications. Mechanical strength to impacts IK10 (20 joule). Glow-wire test resistance 850°C. ELECTRICAL Halogen Free electronic wiring 230V-50/60Hz, power factor 0.95, THD <25%, constant output current, SELV, class I, 1 driver. Power of the luminaire 40 W. CE - IEC 60598-1 - EN 60598-1. SAFE FLICKER: PstLM=<1 and SVM=<0.4 (IEC TR 61547-1 and IEC TR 63158), to ensure a more comfortable and safe light. Luminaire compliant with EN 60598-2-22 for power supply from a centralised emergency system CPSS (Central Power Supply System), not incorporated in the luminaire - high risk areas excluded. The default power and flux are 100% in AC and 100% in DC. Ambient temperature from -20°C to +40°C. Temperature class T6 max 85°C. Quick connection via M20x1.5 cable gland in fibreglass reinforced polyamide with 2m H07RN-F 3G1.5mm<sup>2</sup> cable. Relative humidity UR: <95%. INSTALLATION Ceiling / Suspended / Wall. All accessories dedicated to this product are available on the Catalog and on our website [www.3F-Filippi.com](http://www.3F-Filippi.com). APPLICATIONS Environments with ATEX explosive atmosphere (Conformity 2014/34/UE, EN IEC 60079-0, EN 60079-31): Group II, Category 3D (Ex Tc IIIC T85°C Dc). Suitable product for food production plants (HACCP), IFS (Food Version 6), BRC (GSFS Food Version 7). Severe Industrial Environments, food and agri-food industries, scientific and food processing laboratories, environments with high humidity, swimming pools, railway, aeronautical and port applications. In environments with temperature from -20°C to +40°C with a humidity degree up to 95%, except the ones where the luminaire materials are unsuitable. Body resistant to the following substances: Ethyl alcohol (24 hours at 20°C), aqueous detergents, hydrochloric acid (produces a slight halo), DOT4 brake oil, sulfuric acid (produces a slight halo), ammonia. When using this data, remember that it is the result of laboratory tests, and therefore valid only under those test conditions: the data is to be considered approximate and, in the absence of practical experience, it is advisable to carry out tests under actual operating conditions. Temperature and concentration of the chemical agent can affect materials and influence LED technology. For applications in environments in which disturbances on the power network may be present and/or involve use at low temperatures, surge protection devices should be fitted on the power supply and any causes of undervoltages eliminated. For specific applications please contact our technical offices. WARNING Luminaire designed for disposal/recycling at end-of-life. Replaceable (LED only) light source by a professional. Replaceable control gear by a professional.

Light output 1 (integrated)



Lamp type	LED	CCT	6500 K
Nominal lamp power	40 W	CRI	80
Total flux	6209 lm	LOR	100%
Luminous efficacy	155 lm/W	Total power	40 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 49.76 in

Diameter: 3.15 in

Adjustability

Fixed

Electric

System power: 40 W

Appliance Class: I

Protection

IP: 66