


Product data sheet

VIGILANT LED HIGH BAY 14000 LUMENS, MEDIUM DISTRIBUTION, CLEAR POLYCARBONATE LENS
HEX4MC2BXXXXXN
DIALIGHT



Vigilant LED High Bay 14,000 Lumens 102 Watts 100-277V AC, 120-250V DC Cool White, 80CRI Clear Polycarbonate Lens UL 1598/A (wet locations) CSA C22.2 No. 250 NEMA 4X CE, ENEC EN 60598-1:2015 EN 60598-2-1 (ed. 1), IEC 60598-2-1 (ed. 8) EN 60598-2-24:2013 EN 62471:2008, EN 62778:2014 EN 62493:2015 IEC60068 Salt Spray Testing - Severity 1 D-Marking to EN 60598 2-24 IK10 Medium Distribution IP66/67 LM-79 Tested IES File

Light output 1 (integrated)



Lamp type	LED	CCT	5181 K
Nominal lamp power	98.7 W	CRI	80
Total flux	14583 lm	LOR	100%
Luminous efficacy	148 lm/W	Total power	98.7 W

Mounting mode

Pendant

Shape and measurements

Height: 3.00 in
Diameter: 15.96 in

Adjustability

Rotatable, Tilttable

Electric

System power: 98.7 W
Voltage: 240 V AC, 120 V AC, 277 V AC, 110 V AC, 230 V AC
Appliance Class: I

Protection

IP: 66
IK: 10