Product data sheet


TOP ELEMENT 200-2 AS L3.3 UP 3000K
16.02300.0VXXX
HESS



IP 65


For column light City Elements 200-2 Consisting of: Housing and top cap made of aluminum ø 200 mm. Element height 525 mm. Insert made of plastic (ABS) with lateral light emission, painted black. Cover made of plastic (PMMA), inner edge black

Light output 1




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2433 lm	Total flux	2433 lm
Luminous efficacy	90 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	602 lm	Total flux	602 lm
Luminous efficacy	22 lm/W	Total power	27 W
CCT	3000 K		
CRI	70		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2096 lm	Total flux	2096 lm
Luminous efficacy	78 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	718 lm	Total flux	718 lm
Luminous efficacy	27 lm/W	Total power	27 W
CCT	3000 K		
CRI	70		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2476 lm	Total flux	2476 lm
Luminous efficacy	92 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2038 lm	Total flux	2038 lm
Luminous efficacy	75 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	832 lm	Total flux	832 lm
Luminous efficacy	31 lm/W	Total power	27 W
CCT	3000 K		
CRI	70		




1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2453 lm	Total flux	2453 lm
Luminous efficacy	91 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	492 lm	Total flux	492 lm
Luminous efficacy	25 lm/W	Total power	20 W
CCT	3000 K		
CRI	70		




1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	587 lm	Total flux	587 lm
Luminous efficacy	29 lm/W	Total power	20 W
CCT	3000 K		
CRI	70		



1 x LED

Nominal lamp power	20 W	LOR	100%
Lamp flux	680 lm	Total flux	680 lm
Luminous efficacy	34 lm/W	Total power	20 W
CCT	3000 K		
CRI	70		



1 x LED

Nominal lamp power	27 W	LOR	100%
Lamp flux	2124 lm	Total flux	2124 lm
Luminous efficacy	79 lm/W	Total power	27 W
CCT	3000 K		
CRI	80		

Mounting mode

Pole top mounted

Shape and measurements

Length: 7.95 in
Width: 7.95 in
Height: 20.67 in

Adjustability

Rotatable, Tiltable

Electric

System power: 20-27 W

Protection

IP: 65