


Product data sheet

FLAT POLYMERO
311943.002.1.191
RZB




IP
40

IK
03

Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of non-yellowing plastic (PMMA), opal. Diffuser fastening: patented push system. Suitable for Ceiling mounting, Wall (surface). Slave luminaire. Can only be operated in combination with corresponding master luminaire. Colour: white Diameter: 300 mm Height: 100 mm Lamp: LED exchangeable Socket: without socket Colour temperature: 3000K Colour rendering index (CRI): 83 System power: 13 W Rated luminous flux: 1150 lm Beam angle Down: 118° Luminous efficiency: 88 lm/W Control gear: Converter not necessary Protection class: I Type of protection: IP 40

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	13 W	CRI	80
Total flux	1150 lm	LOR	74%
Luminous efficacy	88 lm/W	ULOR	20%
		Total power	13 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in
Diameter: 11.81 in

Adjustability

Fixed

Electric

System power: 13 W

Protection

IP: 40
IK: 03