


Product data sheet

FLAT POLYMERO IP44
221157.002.2.76
RZB




IP
43

IK
10

Series: Flat Polymero IP44 PC Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: plastic, white. Diffuser fastening: spring system. Diffuser: plastic (polycarbonate), opal. IP43 ceiling mounted, IP44 wall mounted. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 580, H 160 Lamp: LED Colour Temperature: 4000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK10 (20 Joule) Luminaire flux LED: 5400lm System power: 56W Beam Angle: 118° Number of fittings B10A: 4 Number of fittings B16A: 7 Number of fittings C10A: 7 Number of fittings C16A: 11 Inrush current: 102A Unified Glare Ratio: 21,5 EEC: A++

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	56 W	CRI	80
Total flux	5400 lm	LOR	100%
Luminous efficacy	96 lm/W	ULOR	8%
		Total power	56 W

Mounting mode

Wall mounted

Electric

System power: 56 W

Shape and measurements

Height: 6.30 in
Diameter: 22.83 in

Protection

IP: 43
IK: 10

Adjustability

Fixed