



Product data sheet

RINQ PD 1200 HÄNGELEUCHTE 50W 2700K SILBER MIKROPRISMEN
445-9012013280V1
MOLTO LUCE




RINQ HÄNGELEUCHTE aus Aluminium, silber, ähnlich RAL 9006, mikroprismatische PMMA-Abdeckung für ausgezeichnete Entblendung
Lichtaustritt direkt, UGR <19, mit Betriebsgerät, Kabel transparent, Pendellänge 4000mm IP20

Light output 1 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 2 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 3 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 4 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 5 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 6 (integrated)




Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 7 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Light output 8 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	6 W	CRI	80
Total flux	621 lm	LOR	100%
Luminous efficacy	104 lm/W	Total power	6 W

Mounting mode

Pendant

Shape and measurements

Length: 47.24 in

Width: 47.24 in

Height: 3.15 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: Silver gray

Electric

System power: 48 W

Appliance Class: I

Protection

IP: 20

IK: 02