


# Product data sheet

DWIDE CEILING DIRECT 1200 840 CLO  
22331-402  
FAGERHULT



Installation Ceiling mounted or pendant cord. For installation in pendant cords, a suspension cord is required, see Accessories. Connection Three Ø 13 mm cable entries fitted with blanking grommets on the top of the luminaire, see dimension diagram. Knockouts at each end for surface mounted mains cable. 5-way snap-in terminal block at one end of the luminaire, 1-phase through-wiring possible. Design Metal luminaire body with die-cast metal ends, white (RAL 9016) finish. For indirect light, the top is covered by an opal diffuser, which also works as a dust cover. Louvre Delta – Microprism louvre in acrylic (PMMA) with a thin opal diffuser in acrylic (PMMA) inside. Light divider in acrylic (PMMA). Light distribution Direct 100 or Direct/Indirect 90/10.

## Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	25 W	CRI	80
Total flux	3000 lm	LOR	100%
Luminous efficacy	120 lm/W	Total power	25 W

## Mounting mode

Ceiling mounted

## Electric

System power: 25 W

## Shape and measurements

Length: 49.07 in  
Width: 7.88 in  
Height: 1.62 in

## Protection

IP: 20

## Adjustability

Fixed

## Design

Color of housing: White