


Product data sheet

CAMU/95-40° LED - MIRO-SILVER® REFLEKTOR FACETTIERT HOCHGLÄNZEND | MIRO-SILVER® HIGH GLOSS FACETED R..
4400-1900 940 3572LM ETM VW RAL 9016 (37811044140)
REGIOLUX



Spotlight; LED conductor rail spotlight, compact spotlight unit made of die-cast aluminium with thermally separated driver housing on the hinged arm with powder-coated housing. Housing colour traffic white RAL 9016; Light distribution Wide-Beam by means of MIRO-SILVER® High gloss faceted reflector of MIRO-SILVER Aluminium. Suitable for VDU workstations, 65° < 3000 cd/m² omnidirectional glare reduction in accordance with current DIN-EN 12464-1 standard. The light source and driver are removable in accordance with the EU 2019/2020 ecodesign requirements and can be replaced in the factory. Electrical connection via In-Track driver. Luminaire including LED and driver. For busbar system Regiolux DPS/DPSN/DPSNA. Compatible for all ONETRACK 3 rail systems from Global Trac, Eutrac, Iguzzini, Ivela, Reggiani, Targetti. Dimensions (LxWxH): 95mm x 150mm x 176mm Beam angle: 40° (Standardreflektor) (Standardreflektor) Placement: LED, Colour rendering/Light colour CRI ≥ 90 / 4000K Colour tolerance: 2SDCM Photobiological safety (Luminaire): RG1 LED service life: 50000h L90/B10 (Tq 25°C) Nominal luminous flux/switching steps: 4400lm/32W, 4100lm/29W, 3900lm/27W, 3600lm/25W, 3300lm/23W, 3000lm/21W, 2700lm/18W, 2400lm/16W, 2200lm/14W, 1900lm/12W Luminaire luminous efficiency: 139lm/W-155lm/W Controller: Electronic multi-lumen driver, 10-steps (1 pcs.) System output: 32W-12W Mains voltage: 230V Mains frequency: 50Hz Impact resistance (IK rating): IK02 Ambient temperatur: ta 25°C UGR lat./long.: 18.0 / 18.5 (32W) Certification mark: IP20, Protection class II, γ 65°<3000 cd/m², F, Indoor, CE Warranty period: 5 years Regiolux GmbH Type: camu/95-40° LED 4400-1900 940 ETM vw RAL 9016 Article number: 37811044140 Product deep link: <https://www.regiolux.de/en/article/37811044140> General warranty conditions: www.regiolux.de/en/Service/Warranty

Light output 1 (integrated)



Lamp type		CCT	4000 K
Nominal lamp power	24.9 W	CRI	90
Total flux	3572 lm	LOR	100%
Luminous efficacy	143 lm/W	Total power	24.9 W

Mounting mode

Ceiling mounted, Contact rail

Shape and measurements

Height: 6.93 in
Diameter: 3.74 in

Design

Color of housing: White

Electric

System power: 24.9 W
Appliance Class: I

Protection

IP: 20
IK: 02
Designation labels: CE