


# Product data sheet

FLAT POLYMERO SUPER XXL  
311954.002.76  
RZB



Series: Flat Polymero Super XXL Type of Protection: IP 40 Protection Class: I Voltage: 220 - 240 V / 0 Hz, 50 - 60 Hz Base: metal, powder-coated. Diffuser fastening: sash lock, plastic. Diffuser: plastic (PMMA), opal. Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 1700, H 300 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 20200lm System power: 280W Beam Angle: 116° Number of fittings B10A: 8 Number of fittings B16A: 13 Number of fittings C10A: 14 Number of fittings C16A: 22 Inrush current: 53A Unified Glare Ratio: 18,4 EEC: A++

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	280 W	CRI	80
Total flux	20200 lm	LOR	100%
Luminous efficacy	72 lm/W	ULOR	9%
		Total power	280 W

## Mounting mode

Wall mounted

## Shape and measurements

Height: 11.81 in  
Diameter: 66.93 in

## Adjustability

Fixed

## Electric

System power: 280 W

## Protection

IP: 40  
IK: 07