


Product data sheet

TAREK S
741868.004.76
RZB



Series: Tarek Type of Protection: IP 20 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing: powder coated die cast aluminium. Rotates 356° horizontally and swivels 180° vertically, passive cooling. Reflector: faceted aluminium. LED included, with DALI adapter for 230V RZB 3 circuit DALI tracks, anti-reflective safety glass, ceiling mounted. Available Colours: silver, metallic Type of Installation: Track on ceiling Dimensions: L 290, B 120, H 178 Lamp: LED Life time: 50000 h (L80/B10) Colour Temperature: 3100K Socket 1: without socket Operating Mode Lamp 1: Converter, dimmable, DALI Safety Marks: F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 3750lm System power: 45W Beam Angle: 23° Number of fittings B10A: 12 Number of fittings B16A: 20 Inrush current: 30A Unified Glare Ratio: 17,2 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3100 K
Nominal lamp power	45 W	CRI	90
Total flux	3750 lm	LOR	100%
Luminous efficacy	83 lm/W	Total power	45 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 4.72 in
Width: 11.42 in
Height: 7.01 in

Adjustability

Rotatable, Tilttable

Electric

System power: 45 W

Protection

IP: 20
IK: 07