


Product data sheet

LIGHT LINEAR PT 4 STREET AND AREA LUMINAIRES
LI-21172-LC-T4-W40
LIGMAN



- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing and extruded aluminium column pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Maximum wind load resistance is 100 km/h - Surge protection 10 kV

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 4032 K |
| Nominal lamp power | 105 W | CRI | 80 |
| Total flux | 12517 lm | LOR | 100% |
| Luminous efficacy | 119 lm/W | Total power | 105 W |

Mounting mode

Standing / Bollard, Pole top mounted

Shape and measurements

Length: 39.37 in
Width: 5.91 in
Height: 3.54 in
Weight: 29.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 105 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C