
Product data sheet

LUCAS X (1-ARMED) 9.850.3046.15 LEIPZIGER LEUCHTEN



Mounting heights between 4.00 - 6.00 m. - High-quality mirror optics to suit non-glare class KB1 - Aluminium cast luminaire body, inside white, outside painted in colour - Impact-resistant polycarbonate attachment, UV-stabilized, transparent or beaded - Luminaires with wiring ready for connection - Easy installation with adapter jack - Scope of supply includes complete unit with one/two painted special steel brackets - Available in any RAL or DB colour without surcharge - Pole for single-bracket luminaire: dia. 76 mm, please order separately inquire separately for pole to suit double-bracket luminaire Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet


Light output 1



1 x High pressure mercury vapour lamp	1 x High	pressure	mercury	vapour	lamp
---------------------------------------	----------	----------	---------	--------	------

IP 55

Nominal lamp power	50 W	LOR	84%
Lamp flux	2000 lm	Total flux	1675 lm
Luminous efficacy	28 lm/W	Total power	59 W
CCT	3400 K		
CRI	54		



1 x High pressure mercury vapour lamp			
Nominal lamp power	80 W	LOR	

Nominal lamp power	80 W	LOR	84%
Lamp flux	4000 lm	Total flux	3351 lm
Luminous efficacy	38 lm/W	Total power	89 W
CCT	3400 K		
CRI	54		

Mounting mode	Electric
Pole top mounted	System power: 59-89 W
Shape and measurements	Protection
Height: 19.69 in	IP: 55
Diameter: 22.44 in	