


Product data sheet

CIRCULAR INWARD 3 RINGS (Ø2000 Ø1200 Ø600)
CD4H-00V9AZOU05
LEDSC4




LedsC4 Circular Inward 3 Rings (Ø2000 Ø1200 Ø600) CD4H-00V9AZOU05V1 Pendant for indoor use. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 0 Product width or diameter (mm): 2074 Product height (mm): 6000 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 227W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. Photobiological risk: RG1. Real flux (lm): 12392. Real lm/W: 53. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 234. Power factor: 0.90. Dimmable equipment included: ON-OFF.

Light output 1




1 x LED			
Nominal lamp power	127 W	LOR	100%
Lamp flux	6459 lm	ULOR	50%
Luminous efficacy	51 lm/W	Total flux	6459 lm
CCT	2700 K	Total power	127 W
CRI	90		

Light output 2



1 x LED			
Nominal lamp power	69.5 W	LOR	100%
Lamp flux	3708 lm	ULOR	50%
Luminous efficacy	53 lm/W	Total flux	3708 lm
CCT	2700 K	Total power	69.5 W
CRI	90		

Light output 3



1 x LED			
Nominal lamp power	37.5 W	LOR	100%
Lamp flux	2225 lm	ULOR	50%
Luminous efficacy	59 lm/W	Total flux	2225 lm
CCT	2700 K	Total power	37.5 W
CRI	90		

Mounting mode

Pendant, Table luminaire

Shape and measurements

Length: 78.74 in
Width: 78.74 in
Height: 1.18 in

Adjustability

Fixed

Electric

System power: 234 W
Appliance Class: I

Protection

IP: 20