

# Product data sheet

LIGHTSTREAM LED MIDI

721717.004

RZB



IP  
65


IK  
07



Series: Lightstream LED Type of Protection: IP 65 Protection Class: I Voltage: 220 - 240 V / 50 - 60 Hz Housing of corrosion resistant die-cast aluminium for outdoor use, bracket aluminium, powder coated, cover toughened glass with ceramic coating, high efficient narrow beam optics with discrete refractors, with Gore# Protective Vents membrane valve, class I electrical, IK07, IP65, piano key terminal 3x2,5mm<sup>2</sup>, for max. cable Ø 13mm, second cable gland for loop-through available as accessory. Available Colours: silver, metallic Type of Installation: universal mounting system Dimensions: L 267, B 142, H 336 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Regulated power supply Safety Marks: D-mark, F-mark Impact Protection: IK07 (2 Joule) Luminaire flux LED: 2900lm System power: 51W Beam Angle: 12° Number of fittings B10A: 18 Number of fittings B16A: 30 Number of fittings C10A: 31 Number of fittings C16A: 51 Inrush current: 10A Unified Glare Ratio: 6,0 EEC: A

---

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	51 W	CRI	80
Total flux	2900 lm	LOR	100%
Luminous efficacy	57 lm/W	Total power	51 W

---

## Mounting mode

Ceiling mounted

## Shape and measurements

Length: 5.59 in

Width: 10.51 in

Height: 3.54 in

## Adjustability

Tilttable

## Electric

System power: 51 W

Appliance Class: I

## Protection

IP: 65

IK: 07