

Product data sheet

NORA III (W. SHIELD ON SIDE FACING BUILDING OPAL ATTACHMENT)

9.773.3042.36


LEIPZIGER LEUCHTEN



IP
55

For medium light requirements, mounting height 3.50 - 4.00 m. - Impact-resistant clear or beaded polycarbonate attachment, UV-stabilized - Special reflector of premium highest-grade aluminium, burnished and anodized, for excellent illumination and glare protection - Aluminium luminaire body, inside finished in white paint, outside painted in colour - Aluminium unit carrier , painted white - Adapter jack connection - Available in any RAL or DB colour without surcharge - Scope of supply includes special steel post bracket, painted -Order post dia. 60 mm/ dia. 76 mm separately Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensatet

Light output 1



1 x High pressure mercury vapour lamp

Nominal lamp power	80 W	LOR	84%
Lamp flux	4000 lm	ULOR	3%
Luminous efficacy	38 lm/W	Total flux	3343 lm
CCT	3400 K	Total power	89 W
CRI	54		

Mounting mode

Pole top mounted

Shape and measurements

Height: 11.81 in

Diameter: 21.26 in

Electric

System power: 89 W

Protection

IP: 55