

# Product data sheet


RICHARD IV DA LED (OPTIC 138)  
4.892.8212.184138-3  
LEIPZIGER LEUCHTEN



IP  
65

• recommended pole height 3.00m - 6.00m • luminaire head with canopy made of aluminium; with a special white, reflective underside finish; base made of corrosion-resistant cast aluminium; powder coated • optionally wall bracket with wall shield made of hot-dip galvanised steel and cap made of aluminium; powder coated • glazing made of PMMA RESIST, clear, high-impact-resistant • completely wired; via a plug and socket connector below the luminaire head • for top entry  $\varnothing$  60mm or  $\varnothing$  76mm; wall luminaire: to be screwed on the wall • to be ordered separately: cable, pole, pole accessories, fixing material for the wall installation, back light shield for no glare on the rear side

## Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	23 W	CRI	70
Total flux	2814 lm	LOR	100%
Luminous efficacy	122 lm/W	ULOR	5%
		Total power	23 W

## Mounting mode

Pole top mounted

## Shape and measurements

Height: 22.05 in  
Diameter: 7.87 in  
Weight: 8.9 kg

## Adjustability

Height adjustable

## Design

Color of housing: Other colors

## Electric

System power: 23 W

## Protection

IP: 65