



Product data sheet

PLAY DECO ASYMMETRICAL SQUARE FIXED EMERGENCY
AG29-P7X9M2D3WJ
LEDSC4




LedsC4 Play Deco Asymmetrical Square Fixed Emergency AG29-P7X9M2D3WJ Downlight For downlighting. Structure material: Aluminium, Polycarbonate. Structure finish: Gold/Gold. Diffuser material: Methacrylate. Diffuser finish: Transparent. Warranty: 5 Years. Product net weight (Kg): 0.94 Product length (mm): 110 Product width or diameter (mm): 110 Product height (mm): 92 Ø of the hole for recessing (mm): 100 Permitted ceiling thickness: 0-25 Class 2. Luminaire not suitable for coating with insulation materials. Glow wire test: 850. IP: IP54. IK: IK03. LED. No. of lampholders or LEDs: 1. LED brand: CREE. Driver brand: VOSSLOH-SCHWABE. Maximum power of light source: 6.4W. Colour temperature: 4000K. Colour rendering index: 90. MacAdam Steps: 2. Hours of life: 50.000h L80B20. Photobiological risk: RG2. % de Flickering: <5%. Real flux (lm): 543. Real lm/W: 64. Voltage / frequency range: 100-240/50-60Hz. Voltage: 9. Equipment included: Yes. Total power: 8.5. Power factor: 0.90. Dimmable equipment included: DALI-2/PUSH. Emergency supply provision.

Light output 1 (emergency)



1 x LED			
Nominal lamp power	2.13 W	LOR	100%
Lamp flux	136 lm	Total flux	136 lm
Luminous efficacy	64 lm/W	Total power	2.13 W
CCT	4000 K		
CRI	90		



1 x LED			
Nominal lamp power	8.5 W	LOR	100%
Lamp flux	543 lm	Total flux	542 lm
Luminous efficacy	64 lm/W	Total power	8.5 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 4.33 in
Width: 4.33 in
Height: 0.08 in

Electric

System power: 2.13-8.5 W
Appliance Class: II

Information regarding emergency functions

Emergency lighting only
Emergency sign: N/A

Adjustability

Fixed

Protection

IP: 54

IK: 03