

Product data sheet


KAP 105
03.4401.B1/CDM-TC/20W/35W
FLOS



IP
44


Luminaire with embedded installations on ceilings for halogen lamps, metal halide and LED. The Easy Kap version, incorporates body injected in zamak with liquid paint finish and outer diameter of 105mm with opal glass diffuser. Pre-frame instalation not necessary. The Kap version incorporates body injected in aluminium with liquid paint finish. It is available in two sizes: 105mm and 145mm, always in No Trim installation. Main view made of anodized gloss aluminium with diffuser element made in borosilicate glass. Lampholders with heatsink element in injected aluminium and embedment ring of the optical body in thermoplastic material. Finishings: white (B1), matt gold (GL), blue (BU) and black (74).

Light output 1



1 x Metal halide lamp

Nominal lamp power	35 W	Socket	G8D.5
Lamp flux	3300 lm	LOR	33%
Luminous efficacy	31 lm/W	Total flux	1102 lm
CCT	3000 K	Total power	35 W
CRI	84		



1 x Metal halide lamp

Nominal lamp power	20 W	Socket	G8D.5
Lamp flux	1700 lm	LOR	33%
Luminous efficacy	26 lm/W	Total flux	567 lm
CCT	3000 K	Total power	22 W
CRI	83		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 9.06 in
Diameter: 4.13 in

Adjustability

Fixed

Electric

System power: 22-35 W

Protection

IP: 44