

Product data sheet


A20-S620 LED 3500 840
GLAMOX



IP
20

Light source LED A20-S320: LED 1300 lumen out A20-S420: LED 2400 lumen out A20-S620: LED 3500 lumen out Light source information: 3000/4000 Kelvin, CRI 80, MacAdams 3. Lifetime LED: Up to 60.000h Ta25. For precise technical information please see the data sheet on item level. (Use <Find your version> on right side) Driver Electronic ballast (HF) or DALI. Driver life time up to 100.000 h/10 % (max failure) at Ta 25°C Body material & colour Housing in die-cast aluminium, painted in polyester powder paint in colour grey (RAL 9006). Opal satin acrylic diffuser. Mounting Surface mounted luminaire for installation on the ceiling or wall. Connection 5 pole push-in terminal block prepared for through wiring. Integrated sensors This product is available with a Microwave sensor type SMR-SEN with relay based ON/OFF switch or a Microwave sensor wired for Corridor function type SMC-SEN. For more information see user manual for the respective sensor under "Download".

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	39 W	CRI	80
Total flux	3499 lm	LOR	100%
Luminous efficacy	90 lm/W	ULOR	9%
		Total power	39 W

Mounting mode

Ceiling mounted

Shape and measurements

Height: 4.33 in

Diameter: 24.41 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 39 W

Protection

IP: 20