


Product data sheet

HANDRAIL LUMINAIRE 93011 LED (Ø 42,4X2) @700MA
40071355046
EATON EMERGENCY LIGHTING




HandRail 93011 LED handrail mounting with 70° asymmetric optics, indoor and outdoor applications, for installation into 42 mm Dia. handrail
* (Does not include driver) • Safety luminaire in LED technology for mounting into handrail • Can be mounted in stainless steel, galvanized steel or plastic handrail • Discrete mounting for improved aesthetics • Superior spacing due to optics technology and highly efficient HighPower LEDs • Suitable for indoor and outdoor applications • Up to 11 m from luminaire to luminaire with optics for open area illumination • Minimum service requirement due to high service life of the LEDs (50,000 hours)

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.1 W	CRI	80
Total flux	235 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	2.1 W

Light output 2 (integrated, emergency)



Lamp type	LED	CCT	4000 K
Nominal lamp power	2.1 W	CRI	80
Total flux	235 lm	LOR	100%
Luminous efficacy	112 lm/W	Total power	2.1 W

Mounting mode

Pole integrated

Shape and measurements

Length: 3.94 in
Width: 1.18 in
Height: 1.57 in

Adjustability

Fixed

Electric

System power: 4.2 W
Appliance Class: II

Information regarding emergency functions

Supplementary emergency lighting
Emergency power supply: Central battery feed-in
Emergency sign: N/A

Protection

IP: 66

IK: 07