
Product data sheet

THINDR 1744.CEN.3

PSM LIGHTING









built-up ceiling light - fixed - central feeding - with LED driver

Light output 1 (integrated)




Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 2 (integrated)



Lamp type	LED	CCT	3114 K
Nominal lamp power	3.8 W	CRI	80
Total flux	285 lm	LOR	100%
Luminous efficacy	75 lm/W	Total power	3.8 W

Light output 3 (integrated)



LED	CCT	3114 K
3.8 W	CRI	80
285 lm	LOR	100%
75 lm/W	Total power	3.8 W
	3.8 W 285 lm	3.8 W CRI 285 lm LOR

Mounting mode

Ceiling mounted

Shape and measurements

Length: 44.49 in Width: 1.77 in Height: 35.83 in

Adjustability

Fixed

Design

Material impression: Matt Color of housing: Other colors Designer: Saskia Mortier Electric

System power: 11.4 W Appliance Class: I

Information regarding emergency functions

Supplementary emergency lighting

Emergency sign: N/A

Protection

IP: 20 IK: 02