Product data sheet

SINUS CURVED SEGMENT DI SILVER PRISM. 45° R920
P33-A44-9006E1840H3M OHNE FOLIE/WITHOUT FOIL
PLANLICHT



IP 40

high output LED 4000K CRI 90 18,3W 1997lm¹ DALI ¹Values without foil [Luminaire is delivered with optional satined-foil for increased homogenity. The light distribution is thus influenced and the luminous flux is reduced by 26,3% https://katalog.planlicht.com/en-gb/search?q=sinus%20segment

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.1 W	CRI	90
Total flux	666 lm	LOR	100%
Luminous efficacy	109 lm/W	Total power	6.1 W

Light output 2 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.1 W	CRI	90
Total flux	666 lm	LOR	100%
Luminous efficacy	109 lm/W	Total power	6.1 W

Light output 3 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	6.1 W	CRI	90
Total flux	666 lm	LOR	100%
Luminous efficacy	109 lm/W	Total power	6.1 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 26.57 in

Width: 12.95 in

Height: 3.94 in

Adjustability

Fixed

Electric

System power: 18.3 W

Protection

IP: 40