


Product data sheet

FLAT BASIC
251037.002
RZB




IP
43

IK
03

Series: Flat Basic Type of Protection: IP 43, IP 44 Protection Class: I Voltage: 220 - 240 V / 50 Hz Armatur Aluminium-Druckguss pulverbeschichtet. Abdeckung Glas opal seidenmatt, mundgeblasen. Glasbefestigung durch Bajonettverschluss. Leuchtmittel (LED) im Lieferumfang enthalten. Dekorning nicht möglich! Available Colours: white Type of Installation: Ceiling mounting, Wall (surface) Dimensions: D 300, H 106 Lamp: LED Colour Temperature: 3000K Socket 1: without socket Operating Mode Lamp 1: Converter not necessary Safety Marks: F-mark Impact Protection: IK03 (0,35 Joule) Luminaire flux LED: 360lm System power: 12W Beam Angle: 118° Unified Glare Ratio: 15,3 EEC: A+

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	12 W	CRI	80
Total flux	360 lm	LOR	100%
Luminous efficacy	30 lm/W	ULOR	19%
		Total power	12 W

Mounting mode

Ceiling mounted

Electric

System power: 12 W

Shape and measurements

Height: 4.17 in
Diameter: 11.81 in

Protection

IP: 43
IK: 03

Adjustability

Fixed