Product data sheet

VOLKMAR II (WALL FITTING) 9.840.0087.05 LEIPZIGER LEUCHTEN






CRI

For medium light requirements, mounting heights from 3.00 - 4.00 m. - Luminaire body made of aluminium/galvanized steel sheet - Impactresistant clear polycarbonate attachment, UV-stabilized - Steel tubing galvanized and painted - Adapter jack connection -Available in any RAL or DB -colour without surcharge Voltage: 230V 50Hz Protected to: IP 55 Protection class: I/II Made to DIN VDE 0711 Luminaires generally compensated

Light output 1



1 x High pressure sodium vapour lamp					
Nominal lamp power	100 W	LOR			
Lamp flux	10400 lm	ULOR			
Luminous efficacy	77 lm/W	Total flux			
CCT	2000 K	Total power			

25

$X / Y \perp / Y$	$\sim \times$
XATAA	\sim
IXX HIX	$\times $ \setminus
	>
$I \land X \land X \land X \land X$	\sim
L / / X X U	1 1 7
MALAXXIIIXXA	+
	17-1
	/ /
	$\sim /$
	14
$(\setminus X \vee T + T \vee Y$	17
	\checkmark /
$\sim \times / \top / \times /$	\sim
$\wedge \times \gamma + \gamma \times$	\sim
	$\sim \times$

1 x High	pressure sodium vapour lamp

Nominal lamp power	70 W	LOR	85%
Lamp flux	5600 lm	ULOR	28%
Luminous efficacy	57 lm/W	Total flux	4739 lm
CCT	2000 K	Total power	83 W
CRI	25		

Wall mounted

Shape and measurements

Height: 16.14 in Diameter: 16.14 in Electric System power: 83-115 W Protection

IP: 55

85% 28% 8802 lm 115 W