
Product data sheet

T-BAR RECESSED LUMINAIRE, MICRO PRISM COVER
TB3102101-30-30
SCHMITZ | WILA








T-BAR LED 3000 K Recessed Luminaire, Light distribution direct Micro Prism for ceiling grid 625 mm, 24 mm visual T-grids Product: TB3102101-30-30 Operating technology: independent driver required Light Technique Micro prismatic cover with symmetrical lighting distribution, PMMA CRI > 80 Color temperature 3000K 50.000 h lifetime (L70) Luminaire housing Housing made of anodized aluminum extrusion body, visible surfaces white- coated (RAL 9003) Luminaire length 625 mm; optimized for standard suspended grid ceiling systems 625 mm, 24 mm visual T-grids Operating and assembly technology Connecting cable with quick connectors to each side for multiple product connections LED driver to be ordered separately e T-BAR replaces selected cross tees of the grid ceiling system Brackets at each end for an easy installation Precise positioning via slots Lamp Wattage: 17 W Colour Rendering Index: 80 Colour Temperature: 3000 K Luminaire Luminous Flux: 989 Llm System Efficiency: 58 Llm/W Luminance γ ≥ 65°: --- UGR: 25 Number Luminaires LZ: 0.14 Connector: plug-in terminal, 5 x 2.5 mm2, with loop-in function Length: 625 mm Width: 24 mm Height: 15 mm Installation Depth RD: 51 mm Total Weight: 1.2 kg Degree of Protection IP44 CE-Sign Total system: Protection class 2 Data record TB3102101-30-30

Light output 1



1 x General service incandescent lamp

Nominal lamp power	17 W	LOR	100%
Lamp flux	989 lm	Total flux	989 lm
Luminous efficacy	58 lm/W	Total power	17 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling recessed

Shape and measurements

Length: 24.61 in
Width: 0.94 in
Height: 2.01 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 17 W
Appliance Class: II

Protection

IP: 44