Product data sheet

ATHLON OPTIC AREA LIGHT / DOUBLE SIDED 7259-K-3-897-XX

UNILAMP










ATHLON is a series of mini floodlights with wide beam asymmetrical and bi-symmetrical light distribution. It operates with High Power LED module which is attached on aluminium body as a heat sink. The Alanod Miro reflectors used in this luminaire are designed by Photopia highend lighting engineering software. The calibrated aiming unit provides accuracy of the light distribution on the illuminated surface. The range of accessories such as ground mount spike, tree strap and pole clamping unit makes it a dynamic floodlight choice. ATHLON is suitable to light up small to medium sized objects or areas such as signage boards, ceiling, building facades, etc.

Light output 1



1 x LED
Nominal lar
Lamp flux


mp power 25 W 2880 lm Lamp flux 115 lm/W Luminous efficacy CCT 3000 K CRI 80

LOR Total flux

Total power

72% 2070 lm 28 W

Light output 2



1 x LED

Nominal lamp power 25 W Lamp flux 2880 lm Luminous efficacy 115 lm/W CCT 3000 K CRI 80

LOR 72% Total flux 2070 lm Total power 28 W

Mounting mode

Pole top mounted, Pole integrated

Shape and measurements

Length: 9.67 in Width: 4.13 in Height: 9.23 in

Adjustability

Rotatable, Tiltable

Electric

System power: 56 W Appliance Class: I

Protection

IP: 66 IK: 07