



Product data sheet


6639 MADRID S - HE - SUSPENSION-CEILING DIRECT LIGHT - WITH PRISMATIC DIFFUSER 3000K CRI 80 30W CLD-D-D WH
133122-3941

DISANO



Housing: in extruded aluminium. Diffuser: prismatic polycarbonate. Coating: epoxy polyester powder coating resistant to UV rays. Low flicker: luminaire with very low flicker: evenly distributed light for greater visual safety. Photobiological risk: exempt risk group according to EN62471. : EN60598-1. They have a degree of protection according to the EN60529 standard. On request: - emergency wiring CLD E -07. - emergency wiring with centralized power supply CLD EC -0050. - version with pass-through wiring for continuous line modules with subcode -0072: supplied without diffuser, which should be purchased separately with acc. 6078, ideal for continuous and uninterrupted "all light" lines. - black colour version

Light output 1



1 x LED

Nominal lamp power	30 W	LOR	100%
Lamp flux	4275 lm	Total flux	4275 lm
Luminous efficacy	142 lm/W	Total power	30 W
CCT	3000 K		
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 57.68 in

Width: 2.52 in

Height: 2.91 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 30 W

Appliance Class: I

Protection

IP: 40

IK: 07

Designation labels: CE