Product data sheet

SURFACE-MOUNTED DIRECTIONAL SPOTLIGHT NOVO 2 SQUARE INNER RING FLUSH-MOUNTED SQUARE 15.4W 2000LM.. 2011.0452 - NOVO2 SS FM CM135X135 LED2000-940-R60 ALBR ONF


REGENT



IP 20 IK 07

Surface-mounted directional spotlight Novo 2 Square inner ring flush-mounted, with LED, system power: 15.4 W, luminous flux of luminaire 2000 lm, colour rendering index CRI > 90, colour temperature 4000 K, neutral white, colour tolerances SDCM 3, lifetime LED L90 50'000 h, photobiological safety: the luminaire poses no danger (RG0), 230 V, rated current: 43 mA, direct light emission, housing in die-cast aluminium, alu brushed, with reflector, 60, 1 integral control gear, ON/OFF, High-quality die-cast aluminium housing, independent 365° orientation of the individual heads, reduced installation thanks to completely pre-assembled luminaire with power supply unit, through-wiring possible protection class I, ingress protection IP20, glow wire test 850 °C, impact strength: IK 07 this product contains a light source of energy efficiency class D and EPREL registration number: 2026464 L = 135 mm, B = 135 mm, H = 122 mm, swivelling 15°

Light output 1



1 x LED

Nominal lamp power	8.2 W	LOR	100%
Lamp flux	2000 lm	Total flux	1999 lm
Luminous efficacy	244 lm/W	Total power	15.4 W
CCT	4000 K		
CRI	90		

Mounting mode

Ceiling mounted

Shape and measurements

Length: 0.04 in
Width: 0.04 in
Height: 0.04 in
Weight: 1.499 kg

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 15.4 W
Appliance Class: I

Protection

IP: 20
IK: 07