Product data sheet

LARGO WHITE 550LM 3000K RA>80 TRAILING EDGE DIMMING 7021986115697

SG ARMATUREN










Square wall luminaire with extra protection of diffuser. Made of die-cast powder-coated aluminium. Diffuser made of UV-stabilised opal polycarbonate. Two inputs/outputs for cables, option of both visible and concealed cabling, and loopable quick clips. Corrosion-proof with 10year warranty, IP65 and vandal-resistant rating IK10. Light distribution Direct Light technic LED 10W 3000K Ra>80 SDCM 3 L70/B50 >50,000 hrs Control/Dimming Trailing edge dimming Protection Class II IP65 IK10 Fire protection class: 850°C - 30s Materials and finish Housing: Aluminium Colour: White (RAL 9003) Optics: UV-stabilized polycarbonate Mounting/Connection Surface, Indoor / Outdoor Screwless terminal block Max. luminaires per circuit breaker: B10: 33, B16: 52, C10: 40, C16: 64

Light output 1



I X LED	
Nominal lamp power	
Lamp flux	
Luminous efficacy	
CCT	
CRI	

1....

10 W	LOR
550 lm	ULOR
55 lm/W	Total flux
3000 K	Total powe
80	

100%
11%
550 lm
10 W

Mounting mode

Wall mounted

Shape and measurements

Length: 9.45 in Width: 4.57 in Height: 9.45 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 10 W Appliance Class: II

Protection

IP: 65 IK: 10