Product data sheet

LED IT STRIP 982522.002.1

RZB








Series: LED IT STRIP Flexible fully encapsulated LED strip for indoor and outdoor use. UV/IR resistant TPU potting. LED Pitch 18 mm. Solderless connection technology by means of Plug+Play connector system. No need for silicone sealing. Easy separability with commercially available tools (every 130 mm). Smallest bending radius 60 mm. Up to 5 meters LED strip length with only one power supply. One power feed and one end cap included, other accessories can be ordered separately. Colour: white Length: 5000 mm Width: 12 mm Height: 3.4 mm Lamp: LED Socket: without socket Colour temperature: 4000K Colour rendering index (CRI): 80 System power: 12 W Rated luminous flux: 1100 Im Luminous efficiency: 92 Im/W Protection class: III Type of protection: IP 65

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	12 W	CRI	80
Total flux	1100 lm	LOR	100%
Luminous efficacy	92 lm/W	Total power	12 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 0.47 in Width: 196.85 in Height: 0.12 in

Adjustability

Fixed

Electric

System power: 12 W

Protection

IP: 65