Product data sheet

MUSTANG 38 SURFACE HIGH BAY LUMINAIRES
MS-91161-T2-W40
LIGMAN



IP 54 IK 07

- Lamp LED - CRI Ra > 80 - MacAdam Ellipse 3 SDCM - Colour 3000K , 4000K - Formed sheet aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Single cable entry - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear, impact-resistant, toughened glass diffuser - Integral control gear

Light output 1 (integrated)



Lamp type	LED	CCT	4032 K
Nominal lamp power	37.4 W	CRI	80
Total flux	4590 lm	LOR	100%
Luminous efficacy	123 lm/W	Total power	37.4 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 17.72 in
Width: 13.07 in
Height: 3.54 in
Weight: 8.5 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 37.4 W
Voltage: 230 V AC
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 54
IK: 07
Surface temperature: 40°C