


Product data sheet

FLAT LIGHT SURFACE MOUNTED LUMINAIRE
EL1402095-30-40
SCHMITZ | WILA



Flat Light LED 4000 K Surface Mounted Luminaire, Wall Mounted Luminaire, Light distribution direct/indirect Opal Cover Product: EL1402095-30-40 Light Technique Light distribution direct/indirect Colour rendering index CRI > 80 Colour temperature 4000K Life-time 50,000 h (L70/B10) Luminaire housing Housing made of aluminium, painted in white (RAL9016) Frosted cover for softly diffusing the light into the depth of the room Back cover in clear PC Operating and assembly technology LED driver directly integrated Suitable for emergency lighting with central battery Plug-in terminals for through wiring up to 3 x 2.5 mm² Suitable for ceiling and wall installation Top part of the luminaire can be fastened without tools Lamp Wattage: 48 W Colour Rendering Index: 80 Colour Temperature: 4000 K Luminaire Luminous Flux: 4470 Llm System Efficiency: 83 Llm/W Luminance $\gamma \geq 65^\circ$: --- UGR: 23 Number Luminaires LZ: 0.03 Connector: plug-in terminal, 3 x 2.5 mm² Diameter D: 515 mm Height: 77 mm Total Weight: 4 kg Degree of Protection IP20 CE-Sign Total system: Protection class 1 Data record EL1402095-30-40

Light output 1



1 x General service incandescent lamp			
Nominal lamp power	54 W	LOR	100%
Lamp flux	4470 lm	ULOR	4%
Luminous efficacy	83 lm/W	Total flux	4470 lm
CCT	4000 K	Total power	54 W
CRI	80		

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.03 in
Diameter: 20.28 in

Adjustability

Fixed

Design

Color of housing: White

Electric

System power: 54 W
Appliance Class: I

Protection

IP: 20