Product data sheet

SATIN2 MWA L930 36L35 32° 840 KIT
96268073
THORN LIGHTING



A discreet linear floodlight for façade illumination applications. 36 LEDs driven at 350mA with 32° distribution. Remote, Electronic, fixed output control gear making the product suitable for operation in ambient temperatures of up to 50°C. Body: extruded aluminium (EN AW-6060 T6) painted textured silver grey. Sides: grey polycarbonate. Enclosure: UV stabilised polycarbonate. Stirrups: powder coated steel. Class II electrical, IP67, IK08. Surface mounted or recessed with optional ground recessed box. Pre-wired with 1m of 2x1mm² H05RNF cable (or 1m of 5x1mm² Profiplast cable for RGBW versions) at one end. Complete with 4000K LED Dimensions: 932 x 75 x 70 mm Total power: 40 W Luminaire luminous flux: 2747 lm Luminaire efficacy: 69 lm/W Weight: 3.9 kg

Light output 1 (integrated)



Lamp type	LED	CCT	3000 K
Nominal lamp power	40 W	CRI	99
Total flux	2747 lm	LOR	100%
Luminous efficacy	69 lm/W	Total power	40 W

Mounting mode

Wall mounted

Shape and measurements

Length: 36.69 in
Width: 2.95 in
Height: 2.76 in
Weight: 3.9 kg

Design

Material impression: Aluminum
Color of housing: Silver gray

Electric

System power: 40 W
Voltage: 230 V AC
Appliance Class: II

Protection

IP: 67
IK: 08
Designation labels: CE