


Product data sheet

ANGLE 2500 60° E 33 830
19.4130.1311.33
LUXIONA



Indoor luminaire. Assembly: mounted in suspended ceiling. The body material is aluminum. Colour - RAL 9010 (white). Luminaire dimensions: Ø151 x 125 mm. Mounting hole: Ø143 mm. Weight 1,15 kg. Diffuser: hardened transparent glass. Beam angle: (C0-C180) / (C90-C270) - 53,2° / 53,2°. Light source type: LED. Colour of the light 3000 K. SDCM=3. CRI82. Lifetime of LED sources: 50000 h L80/B10. Luminaire luminous flux: 1945 lm. Power of luminaire: 21 W. Luminaire's light efficiency: 92,6 lm/W. Driver: standard on/off (E). Voltage 220..240 V, 50..60 Hz. Power factor cosφ: >0,95. Circuit load capacity: 29 (B10), 47 (B16), 49 (C10), 79 (C16). Operating temperature range: 5 ÷ 30° C. Protection degree: IP20/44. Impact resistant: IK04. Protection against electric shock: II. The luminaire can be made in CLO (Constant Lumen Output) version.

Light output 1



1 x LED			
Nominal lamp power	21 W	LOR	83%
Lamp flux	2448 lm	Total flux	2043 lm
Luminous efficacy	117 lm/W	Total power	21 W
CCT	3000 K		
CRI	82		

Mounting mode

Ceiling recessed

Shape and measurements

Height: 4.92 in
Diameter: 5.94 in

Adjustability

Rotatable, Tilttable

Design

Color of housing: White

Electric

System power: 21 W
Appliance Class: II

Protection

IP: 44
IK: 04

Other operating numbers

Ambient temperature range: 41...86°F