


# Product data sheet

URBINO LED S ED 16W 1950LM 2700K IP66 O20 GRAY I  
 130772.5L141.200  
 LUG



A functionally optimised modern LED luminaire that complements the URBINO LED luminaire family in an environmentally responsible way with solutions for lower power and flux points. Mounting: on pillar, on outriggers, with mounting brackets (to be ordered separately) Body: high pressure die-cast aluminum Lateral Surface Wind Exposed: 0.035 m<sup>2</sup> Power supply efficiency: ≤93% Power: 220-240V 50/60Hz Lifetime LED (L90): 100 000 h Available on request: DALI, DIM 1..10V, knife switch, 10kV surge protection, NTC, NEMA connector, ZHAGA connector, version with increased corrosion resistance in accordance with class C5-M, extension of the warranty to 10 years Warranty: 5 years Application: cycle paths, avenues, sidewalks, parks, parking areas, Railway stations, residential, public spaces, playgrounds, promenade, local roads, town roads, residential area roads, pedestrian crossings Additional information: the standard version of the luminaire is corrosion resistant according to class C4 Other remarks: the pole and boom are not part of the luminaire Type of optics: O20

## Light output 1 (integrated)



Lamp type	LED	CCT	2700 K
Nominal lamp power	16 W	CRI	70
Total flux	1950 lm	LOR	100%
Luminous efficacy	122 lm/W	Total power	16 W

## Mounting mode

Pole top mounted

## Shape and measurements

Length: 18.57 in

Width: 7.82 in

Height: 3.93 in

## Adjustability

Fixed

## Electric

System power: 16 W

Appliance Class: I

## Protection

IP: 66

IK: 10