


Product data sheet

6057/2212-201-6530-121-200
288972
STAHL



"Pendant light fitting LED explosion-protected Type: 6057/2212-201-6530-121-200 Enclosure material: Aluminium Powder-coated Enclosure colour: Light grey (RAL 7035) Protective glass material: Thermally resistant Borosilicate glass Wire guard: No Version: Pendant light fitting Lamp wattage: 25 W Lamp: LED Light colour: 5700K - cold white Colour temperature: 5.700 K Colour rendering: ≥ 80 Light distribution: Wide beam Luminous flux: 3.070 lm Luminaire efficacy: 113 lm/W Dimensions (L x W x H): 234 x 184 x 344 mm AC rated operational voltage: 110 ... 277 V Application range (zones): 1 , 2 , 21 , 22 T85 °C min. ambient temperature: -20 °C max. ambient temperature: +50 °C Degree of protection (IP): IP66 / IP67 Cable glands and entries: According to the order Stopping plugs: According to the order For further information, see: r-stahl.com WebCode 6057B"

Light output 1 (integrated)



Lamp type	LED	CCT	5700 K
Nominal lamp power	27 W	CRI	81
Total flux	3070 lm	LOR	100%
Luminous efficacy	114 lm/W	Total power	27 W

Mounting mode

Ceiling mounted

Shape and measurements

Length: 9.29 in

Width: 8.11 in

Height: 13.62 in

Adjustability

Fixed

Design

Color of housing: Silver gray

Electric

System power: 27 W

Appliance Class: III

Protection

IP: 67

IK: 10

Designation labels: CE