


# Product data sheet

CIRCULAR INWARD Ø1200 RECESSED  
CD5B-00V9AZRU05  
LEDSC4



LedsC4 Circular Inward ø1200 Recessed CD5B-00V9AZRU05V1 Pendant for indoor use. For uplighting and downlighting. Structure finish: Black. Diffuser material: Polycarbonate. Diffuser finish: Opal. Warranty: 5 Years. Product net weight (Kg): 6 Product width or diameter (mm): 1209 Product height (mm): 3000 Ø of the hole for recessing (mm): 100 Class 1. IP: IP20. LED. No. of lampholders or LEDs: 1. Driver brand: MEANWELL. Maximum power of light source: 67.4W. Colour temperature: 2700K. Colour rendering index: 90. MacAdam Steps: 3. Hours of life: 50.000h L80B20. UGR: 7.5. Photobiological risk: RG1. Real flux (lm): 3708. Real lm/W: 52. Voltage / frequency range: 90-305/50-60Hz. Voltage: 2,8. Equipment included: Yes. Total power: 72. Power factor: 0.90. Dimmable equipment included: 0-10V.

## Light output 1



1 x LED			
Nominal lamp power	72 W	LOR	100%
Lamp flux	3708 lm	ULOR	50%
Luminous efficacy	52 lm/W	Total flux	3708 lm
CCT	2700 K	Total power	72 W
CRI	90		

## Mounting mode

Pendant, Table luminaire

## Shape and measurements

Length: 47.24 in  
Width: 47.24 in  
Height: 1.18 in

## Adjustability

Fixed

## Electric

System power: 72 W  
Appliance Class: I

## Protection

IP: 20