Product data sheet

LIGHT LINEAR PT-X 14 STREET & AREA LIGHTING LUMINAIRES
LI-21333-M-7040
LIGMAN



IP 65 IK 08

- Lamp LED - CRI Ra > 70 - MacAdam Ellipse 3 SDCM - Colour 3000K and 4000K - Die-cast aluminium housing pre-treated before powder coating ensuring high corrosion resistance - Stainless steel fasteners in grade 316 - Durable silicone rubber gasket - Clear toughened glass - Integral control gear - Maximum wind load resistance is 260 km/h - Surge protection 10kV

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	208 W	CRI	70
Total flux	30285 lm	LOR	100%
Luminous efficacy	146 lm/W	ULOR	50%
		Total power	208 W

Mounting mode

Pole top mounted

Shape and measurements

Length: 41.34 in
Width: 9.84 in
Height: 3.15 in
Weight: 26 kg

Adjustability

Fixed

Design

Color of housing: Black, White, Silver gray

Glare protection

Glare protection: UGR < 19

Electric

System power: 208 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 65
IK: 08
Surface temperature: 40°C