Product data sheet

NORDSTROM 3 FLOODLIGHTS,PROJECTORS
NOD-50021-N-8040
LIGMAN



IP 66 IK 08

- Lamp LED - MacAdam Ellipse 3 SDCM - CCT / CRI 3000K CRI80, 4000K CRI80 - Die-cast aluminium housing - Pre-treated before powder coating ensuring high corrosion resistance - Thermal heat dissipation body - Single cable entry, through wiring upon request - Stainless steel fasteners in grade 304 with zinc flake coating (ZFC) - Durable silicone rubber gasket - High-efficiency PMMA lens - Clear toughened glass - Integral control gear - Remote box IP-rated is not included for NOD-50002, NOD-50012

Light output 1 (integrated)



Lamp type	LED	CCT	4000 K
Nominal lamp power	21 W	CRI	80
Total flux	2294 lm	LOR	100%
Luminous efficacy	109 lm/W	ULOR	50%
		Total power	21 W

Mounting mode

Standing / Bollard, Wall mounted

Shape and measurements

Length: 4.72 in
Width: 4.72 in
Height: 7.28 in
Weight: 2.7 kg

Adjustability

Free

Design

Color of housing: Black, White, Silver gray

Electric

System power: 21 W
Ballast: ECG
Controller: Dimmable 1..10V, DALI
Appliance Class: I

Protection

IP: 66
IK: 08
Surface temperature: 40°C