


Product data sheet

FLAT POLYMERO
311627.002.8.19
RZB




IP
40

IK
10

Series: FLAT POLYMERO Decorative round surface-mounted luminaire. Base: metal, powder-coated. Diffuser made of plastic (polycarbonate), opal, shockproof. Diffuser fastening: patented push system. Suitable for ceiling mounting, wall (surface). With integrated HF movement sensor. HF detector 5.8 GHz ISM frequency band. Sensitivity/Range: 1-8 m in diameter, adjustable from 20-100%. Time control 1 second to 15 minutes in 8 different levels. Coverage: 120°. Can be used as master luminaire up to 800 W (ohmic load), 500 W (fluorescent lamp, LED) / 400 A, 200 µs. Suitable for outdoor use to a limited extent only, as it is sensitive to all movements. Colour: white Diameter D: 300 mm Height H: 100 mm Lamp: LED Socket: without socket Colour temperature: 3000K Colour rendering index (CRI):80 System power 1: 14 W Rated luminous flux 1: 1500 lm Luminous efficacy: 107 lm/W Control gear: Regulated power supply Protection class: I Type of protection: IP 40

Light output 1 (integrated)



| | | | |
|--------------------|----------|-------------|--------|
| Lamp type | LED | CCT | 3000 K |
| Nominal lamp power | 14 W | CRI | 80 |
| Total flux | 1500 lm | LOR | 100% |
| Luminous efficacy | 107 lm/W | ULOR | 12% |
| | | Total power | 14 W |

Mounting mode

Ceiling mounted

Shape and measurements

Height: 3.94 in

Diameter: 11.81 in

Adjustability

Fixed

Electric

System power: 14 W

Protection

IP: 40

IK: 10